

# ECMAS EGA L65

## 250 kgs

### Packaging

ECMAS EGA L65 is supplied in 250 kgs HDPE barrels.

### Shelf Life

Upto 12 months in our original, unopened, sealed packaging; in a dry and cool place at a temperature of 20°C to 50°C.

### Storage And Handling

**KEEP DRY**



The materials must be stored in a moisture free, cool and dry environment, away from any direct sun-light.

**STACK HEIGHT**



Please avoid stacking of the containers.

Handle the product(s) very carefully during transportation.

## PRODUCTIVITY ENHANCER

### Description

ECMAS EGA L65 is a high-performance Limestone and Mineral additive, formulated for enhancing the grinding action. These are weekly basic aqueous solutions to be added during grinding of limestone and mineral.

### Function

When ECMAS EGA L65 is added to raw limestone, they improve the raw mill grinding action which allows raw mill output improvement at unchanged grinding fineness with consequent reduction in specific power consumption with better PSD in turn helps in better clinker quality.

### Advantages

ECMAS EGA L65 is used in limestone grinding for

- Increased grinding efficiency of the mill.
- Increment in mill output, increase in productivity 6-8% depending upon the mill circuit and type.
- Reduced in specific power consumption and increase the availability for mill maintenance.
- Pack-set is reduced, dry fluidity into silos and trucks are improved.
- Maintenance of Quality parameters with enhancement of particle size distribution (PSD)

### Dosage And Usage

The normal recommended dosage for ECMAS EGA L65 is 600 gm to 1200 gm per ton of material.



address 7-4-124, Gagan Pahad, International  
Airport Road, Hyderabad-500052

phone 040 24360014 /16 /17  
email id info@ecmas.co.in

fax 040-24360023  
website www.ecmas.co.in

### Physical Properties

State	Liquid
Colour	Colourless
pH	8.80 ± 1.0
Relative Density (gm/cc)	1.042 ± 0.02

### Quality Policy

We are committed to provide high quality products to ensure highest performance. Each product comes with ECMAS quality stamp is intended to maximize value addition and performance of the final product. The products are manufactured under a management system independently certified to conform to the requirements of the quality standards of ISO 9001-2015.

### Technical Support

Each user can determine the suitability of this product in their particular mode of operation. An ECMAS representative will be happy to assist in proper selection of all our products available for commercial use.



**address** 7-4-124, Gagan Pahad, International  
Airport Road, Hyderabad-500052

**phone** 040 24360014 /16 /17

**email id** info@ecmas.co.in

**fax** 040-24360023

**website** www.ecmas.co.in